

CENTRIFUGE ยี่ห้อ **MLS รุ่น C2.4K**

- Microprocessor control with AC brushless motor.
- 5 inches colorful LCD display the parameters of speed ,timer, RCF, rotors information, program(memory) information, acceleration & deceleration information and error code information.
- Steel centrifuge body and stainless steel chamber are autoclaveable and resistant detergents and disinfection liquids.
- Gas hinge for lid drop protection.
- Safety electrical lid interlock, door can not open when rotor is running and machine won't run when lid open and error code appears.
- Emergency lid lock release when power failure.
- Heat release holes design reduce the temperature inside the centrifugal chamber on running.
- Window on lid for speed calibration and noise measurement.
- Continuous operation, working continuous according the set time.
- 10 kinds of program (memory) and 10 kinds of acceleration & deceleration for choice. If ask for more programs please specially mentioned when place the order.
- Automatic troubleshooting with indication of error code and alarm on the screen.
- Wide choice of Swing rotors and angle rotors and adapters.
- With CE and ISO9001: 2008, ISO13485 certificate.



SPECIFICATION

Speed range (rpm): 0-2400 rpm adjustable

Max capacity (ml): 16 pcs.

Rcf range (xg): 0-1520xg adjustable

Noise(dba): 58dB(A)

Time range: 1-99 minutes adjustable

Speed accuracy: ± 20 rpm

Dimension(mm): 490x640x400 mm

Net weight (without rotor): 62 KGS

Power supply: AC220~240V, 50/60HZ, 2A, 0.2KW

No.1 Fixed rotor



Capacity: 16 PCS
Max speed: 2,400 rpm
Max RCF: 1,520 xg

No.2 Swing out rotor




Capacity: 4 PCS.
Max speed: 1,500 rpm
Max RCF: 530 xg

No.3 Fixed rotor



Capacity: 8
Max speed: 1,500 rpm
Max RCF: 430 xg

OUR CONTACT

 087-8708915

 salesmylabscale@gmail.com

 www.mylabscale.com