

DO30

Dissolved Oxygen Tester

2014
New
Model



Precision easy operation: all functions operated in one hand.

Large LCD with backlight, Multi-line display for easy reading, Auto-Power Off saves battery after 5 mins non-use.

1*1.5V AAA long battery life

Easy maintenance, simple to change battery and electrode

Floats on water, IP67 rated

Field throw measurement (Auto Lock Function)



CLEAN DO30 Dissolved Oxygen Tester

- Unit display; ppm or %.
- Automatically compensates salinity / barometric after manual input for increased accuracy.
- User replaceable membrane cap (CS49303H1L).

Characterized by the accuracy, economic, easy operation and maintenance, DO30 Dissolved Oxygen Tester offers you the best value dissolve oxygen measurements experiences.

Range	0.00 - 20.00 ppm; 0.0 - 200.0%
Resolution	0.01 ppm ; 0.1%
Accuracy	±2% F.S.
Temp. Range	0 - 100.0 °C / 32 - 212 °F
Working Temperature	0 - 60.0 °C / 32 - 140 °F
Auto Temp. Compensation	0 - 60°C
Calibration	1 or 2 point auto calibrate (0% zero oxygen or 100% in air)
Salinity Compensation	0.0 - 40.0 ppt
Atmospheric Pressure Compensation	600 - 1100 mbar
Auto backlight off	1 minutes
Auto power off	5 minutes without key be pressed
Power	1x1.5V AAA battery
Dimensions	(H×W×D) 185×40×48 mm
Weight	95g
Protection	IP67

Package Sets



DO30A
MDO30 Tester + CS4930 sensor + 1*1.5V AAA Electrode
Package Dimension: L*W*H 210*100*25mm
Weight: 300g